

## H07RN-F Technical Data Sheet



| Rated Voltage | Max. Operating Temperature | Min. Temperature of Installation | Max. Temperature of Short Circuit | Min. Internal Bending Radius | Max. Mechanical Stress |
|---------------|----------------------------|----------------------------------|-----------------------------------|------------------------------|------------------------|
| 450/750V      | 60c                        | -25c                             | 200c                              | 6 x OD                       | 5 Kg/mm                |

|                            |   |
|----------------------------|---|
| <b><u>Conductor:</u></b>   | Class 5 flexible bare copper to EN 60228, IEC 60228   |
| <b><u>Insulation:</u></b>  | EPR (Ethylene-Propylene Rubber) type E14  |
| <b><u>Cores:</u></b>       | 2 Core: Brown, Blue<br>3 Core: Brown, Blue, Green/Yellow<br>4 Core: Grey, Brown, Black, Green/Yellow<br>5 Core: Brown, Blue, Green/Yellow, Black, Grey  |
| <b><u>Sheath:</u></b>      | (PCP) Elastomeric Reticulated Polychloroprene type EM2 or other equivalent synthetic elastomer  |
| <b><u>Standards:</u></b>   | CEI 20-19/4, (HD 22.4-EN 50525-2-21), RoHS 2011/65/UE   |
| <b><u>Application:</u></b> | This cable is suitable for use in dry, humid or moist rooms and in open air. Suitable for use in industrial and agricultural workshop appliances, large boiling installations, heating plates, portable lamps, electrical tools and transportable motors or generators. |

# goldwing

CABLE LIMITED

| Size<br>(No x mm) | Mean Overall Diameter<br>(mm)<br>(± 0.2mm) | Indicative Weight of Cable<br>(g/mm) | Conductor Max. Diameter of wires<br>(mm) | Conductor Max. Resistance<br>(Ohms/KM @ 20c) | Insulation Thickness<br>(mm) | Sheath Thickness<br>(mm) | Current (A) Ratings With Ambient Temp. Lower Than 30c |     |
|-------------------|--|--------------------------------------|--|--|------------------------------|--------------------------|---|-----|
|                   |  |                                      |  |  |                              |                          | *FM   | *FI |
| 2x1               | 8  | 88                                   | 0.210                                    | 19,500                                       | 0.62 - 0.8                   | 1.00 - 1.3               | 15  | 17  |
| 3x1               | 8.7  | 108                                  | 0.210                                    | 19,500                                       | 0.62 - 0.8                   | 1.09 - 1.4               | 15  | 17  |
| 4x1               | 9.7  | 136                                  | 0.210                                    | 19,500                                       | 0.62 - 0.8                   | 1.18 - 1.5               | 13.5  | 17  |
| 5x1               | 11   | 174                                  | 0.210                                    | 19,500                                       | 0.62 - 0.8                   | 1.26 - 1.6               | 13.5  | 17  |
| 1x1.5             | 6  | 52                                   | 0.260                                    | 13,300                                       | 0.62 - 0.8                   | 1.09 - 1.4               | 17.5  | 22  |
| 2x1.5             | 9  | 114                                  | 0.260                                    | 13,300                                       | 0.62 - 0.8                   | 1.18 - 1.5               | 19.5  | 22  |
| 3x1.5             | 9.7  | 139                                  | 0.260                                    | 13,300                                       | 0.62 - 0.8                   | 1.26 - 1.6               | 19.5  | 22  |
| 4x1.5             | 10.9                                       | 178                                  | 0.260                                    | 13,300                                       | 0.62 - 0.8                   | 1.35 - 1.7               | 17.5  | 22  |
| 5x1.5             | 12   | 217                                  | 0.260                                    | 13,300                                       | 0.62 - 0.8                   | 1.43 - 1.8               | 17.5  | 22  |
| 1x2.5             | 6.7  | 69                                   | 0.260                                    | 7,980  | 0.71 - 0.9                   | 1.09 - 1.4               | 24  | 30  |
| 2x2.5             | 10.4                                       | 158                                  | 0.260                                    | 7,980  | 0.71 - 0.9                   | 1.35 - 1.7               | 26  | 30  |
| 3x2.5             | 11.4                                       | 200                                  | 0.260                                    | 7,980  | 0.71 - 0.9                   | 1.43 - 1.8               | 26  | 30  |
| 4x2.5             | 12.7                                       | 253                                  | 0.260                                    | 7,980  | 0.71 - 0.9                   | 1.51 - 1.9               | 24  | 30  |
| 5x2.5             | 14   | 309                                  | 0.260                                    | 7,980  | 0.71 - 0.9                   | 1.60 - 2.0               | 24  | 30  |
| 1x4               | 7.5  | 91                                   | 0.310                                    | 4,950  | 0.80 - 1.0                   | 1.18 - 1.5               | 32  | 40  |
| 2x4               | 12.2                                       | 223                                  | 0.310                                    | 4,950  | 0.80 - 1.0                   | 1.43 - 1.8               | 35  | 40  |
| 3x4               | 13   | 273                                  | 0.310                                    | 4,950  | 0.80 - 1.0                   | 1.51 - 1.9               | 32  | 40  |
| 4x4               | 14.3                                       | 340                                  | 0.310                                    | 4,950  | 0.80 - 1.0                   | 1.60 - 2.0               | 32  | 40  |
| 5x4               | 16   | 426                                  | 0.310                                    | 4,950  | 0.80 - 1.0                   | 1.77 - 2.2               | 32  | 40  |
| 1x6               | 8.3  | 119                                  | 0.310                                    | 3,300  | 0.80 - 1.0                   | 1.26 - 1.6               | 41  | 52  |
| 2x6               | 13.6                                       | 291                                  | 0.310                                    | 3,300  | 0.80 - 1.0                   | 1.60 - 2.0               | 46  | 52  |
| 3x6               | 14.7                                       | 366                                  | 0.310                                    | 3,300  | 0.80 - 1.0                   | 1.68 - 2.1               | 46  | 52  |
| 4x6               | 16.5                                       | 470                                  | 0.310                                    | 3,300  | 0.80 - 1.0                   | 1.85 - 2.3               | 41  | 52  |
| 5x6               | 18.4                                       | 586                                  | 0.310                                    | 3,300  | 0.80 - 1.0                   | 2.03 - 2.5               | 41  | 52  |

\*FM=Free Movement \*FI=Fixed Installation

Unit 8A Ellough Industrial Estate, Beccles, Suffolk, NR34 7TD  
 Tel: 01502 713161 Fax: 01502 717773 Email: sales@goldwingcable.com  
 www.goldwingcable.com